



(800)823-0182 / www.SNAsportsgroup.com

Specifications for Telescopic Pro II

MODEL NO. SNAVB12TP4

Uprights shall consist of an external 3-15/16" outside diameter, anodized aluminum tube and a 3" outside diameter 6061-T6 aluminum telescoping clear anodized inner pole. Inner pole shall move freely up and down to adjustment heights between 6' 6" (storage position) and 8' 2" assisted by an internal spring mechanism to ease adjustment. Upright shall feature pin stop height settings at Men, Women, and Juniors along with intermediate settings added at two inches above Men and Women, and two inches below Juniors. Upright shall feature a sliderail mounted to the inner post which will achieve differing net heights as the spring-loaded inner post moves. Inner post movement shall be spring-assisted. Net tensioning device shall be mounted on the sliderail, and shall be a low profile, threaded rod-type non-slip worm drive linear-actuator type, utilizing conical toothed steel gears for safety and durability. The range of this gear mechanism shall be 17 1/2". Mechanism and threaded rod shall be encased in anodized aluminum. A height adjustment foot shall be permanently attached to the bottom of the external composite tube to allow installation into any 4" diameter floor socket. Adapters to allow installation in 3" and 3.5" sockets shall be available at no additional cost. Standards and winch shall carry no less than a limited lifetime warranty. Entire system shall meet or exceed all NCAA, USVBA, NFHS and FIVB requirements for competition.

VOLLEYBALL FLOOR SLEEVE AND COVER PLATE

MODEL NO. VB27

Aluminum sleeve shall be 13" long. Inside diameter of the sleeve shall be 4". Floor plate shall be the model VB23CV. Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6 31/32" in diameter. Diameter of clear opening shall be 6".

INTERNATIONAL NET WITH RATCHET TENSIONER

MODEL NO. SNAVB1298A

Net shall be 9.8 meters in length and 1-meter maximum width. Netting shall be 10 centimeters square mesh, black nylon, KNOTLESS. Wide side tapes with sewn-in wooden dowels for equal net tension. Top cable shall be 1/8" steel, specially sewn into 50-millimeter white nylon binding. Bottom tension rope shall be nylon, covered by 30-millimeter white nylon binding.

NET ANTENNAE WITH SIDELINE MARKERS

MODEL NO. SNAVB12

Net antennae shall be 3/8" in diameter fiberglass rods, 71" long, with alternating red and white bands. Sideline markers shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to contain antennae. Attachment to the net shall be full-length Velcro closures.

CABLE COVERS

MODEL NO. VB35P

Cable covers shall be made of 1/2" thick polyurethane foam. Shall be covered in 14 oz. reinforced polyester laminated white vinyl.

UPRIGHT SAFETY PADS

MODEL NO. SNAVB51P

Each upright pad shall be a single piece, 72" in height and 26" in width. Padding shall be comprised of cross-linked polyethylene foam, 1.25" thick. Covering shall be nylon-reinforced vinyl. Attachments to uprights shall be affected by Velcro straps. 16 colors available: Scarlet, Cardinal, Maroon, Orange, Burnt Orange, Gold, Vegas Gold, Kelly Green, Forest Green, Columbia Blue, Royal Blue, Dark Royal, Navy Blue, Purple, Gray, Brown, Pink, and Black.