



Specifications for Floor Sleeve Systems

VOLLEYBALL FLOOR SLEEVE

MODEL NO. VB27FS

Aluminum sleeve shall be 13" long. Inside diameter of the sleeve shall be 4".

UNIVERSAL HINGED BRASS COVER PLATE

MODEL NO. VB23CV

Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6 31/32" in diameter. Diameter of clear opening shall be 6".

FLOOR SLEEVE AND COVER PLATE PACKAGES

MODEL NO. VB27

This package shall include both the VB27FS floor sleeve and VB23CV cover plate listed above.

Aluminum sleeve shall be 13" long. Inside diameter of the sleeve shall be 4". Floor plate shall be the model VB23CV. Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6 31/32" in diameter. Diameter of clear opening shall be 6".

MODEL NO. VB23

Aluminum sleeve shall be 9" long. Inside diameter of the sleeve shall be 3". Floor plate shall be the model VB23CV. Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6 31/32" in diameter. Diameter of clear opening shall be 6".

MODEL NO. VB26

Aluminum sleeve shall be 9" long. Inside diameter of the sleeve shall be 3.5". Floor plate shall be the model VB23CV. Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6 31/32" in diameter. Diameter of clear opening shall be 6".