

— Instruction Manual —

PK10P

Pair of Portable Pickleball Systems

PARTS LIST

Item	Qty	Description	Item	Qty	Description
A	2	Vertical Pole	F	8	5/16" Hex Nut
B	2	Brace	G	8	5/16" Lock Washer
C	2	Ballast	H	2	Leveling Pad
D	4	3/8" X 1" Hex Bolt	I	8	5/16" X 2 1/2" Hex Bolt
E	4	3/8" Lock Washer	J	2	Center Net Hold Down

- ◆ Inspect all contents prior to installation. Report any missing parts to dealer immediately.
- ◆ Read all instructions before proceeding.

1. Use the *3/8" X 1" Hex Bolts (D)* and *3/8" Lock Washers (E)* to attach *Brace (B)* to *Ballast (C)*. See illustration.
2. Use the *5/16" X 2 1/2" Hex Bolts (I)*, *5/16" Lock Washers (G)* and *5/16" Hex Nuts (F)* to attach *Vertical Pole (A)* to *Brace (B)*. See illustration.
3. Run the top net rope through the slots on top of *Vertical Pole (A)* and secure them in the top net tie cleat. Tie the bottom net rope around the bottom rope net tie loop.
4. Adjust *Leveling Pad (H)* as needed to achieve desired net height. Official pickleball net height is 36" measured adjacent to the *Vertical Poles (A)* and 34" at the nets center point.
5. Clip *Center Net Hold Down (J)* to the bottom center of pickleball net and adjust until the center measures 34". (Not Shown)

