



Face of soccer goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum 3/4" corner radii for safety and a minimum wall thickness of 1/8". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Soccer goal shall have a 24' wide and 8' high opening. 2 3/8" diameter aluminum football uprights shall extend 10' above the official 10' high horizontal football crossbar and be capable of being installed at either the official 23' 4" high school or 18' 6" college width. Each goal shall include two 11" diameter by 12" wide molded polyethylene ballast drums that act as rear ballast to comply with ASTM F2056 when filled with sand at time of installation. Rear drums shall rotate on a tubular rear horizontal stabilizer bar and serve as transport wheels. Additional standard features shall include molded plastic net attachment clips, 4mm white nets, Velcro net straps and net ground stakes. The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 10' bottom depth. 4" square face of the goal and football uprights and crossbar shall have a white textured polyester powder coated finish. Goal shall carry an 8-year limited warranty. Installation to be completed in accordance to manufacturer's instructions. Do not scale drawings. System shall weight approximately 750#/pair.



PRODUCT SPECIFICATION

SC2480PA44FB SHOOTOUT™ COMBO ALUMINUM FOOTBALL/SOCCER/RUGBY PORTABLE GOALS

REVISED 7/11/17