



## **Specifications for Competition Pickleball System**

### **PICKLEBALL NET SYSTEM**

#### **MODEL NO. PK10XL**

##### **Pickleball Uprights**

3" round tempered, extruded aluminum posts with a green powder-coated finish. Chrome-plated internal winch to tension top cable. Removable crank handle to reduce vandalism or net theft. Meets all IFP and USAPA rules. Complete net system includes posts, net, hold-down strap, and anchor.

##### **Pickleball Net (PK10NXL)**

Official 21'9" x 36" high net with 1.75" mesh. 4mm nylon-coated top cable. Meets all IFP and USAPA rules.

### **Indoor Competition Sleeve and Cover Combo**

#### **MODEL NO. PK23**

##### **Floor Sleeve**

Aluminum sleeve shall be 9" long. Inside diameter of the sleeve shall be 3".

##### **Brass Cover Plate (VB23CV)**

Cover plate shall be brass alloy with attached, hinged cover. Four (4) holes in the ring (for screwing into the floor) shall be completely concealed under the cover when in the closed position. In a floating wood floor, the plate is connected to the floor only allowing it to move with the expansion and contraction of the floor. Plates shall be 8" in diameter. Overall thickness shall be 3/8". Hinged cover plate – not including the outer ring - shall be 6 31/32" in diameter. Diameter of clear opening shall be 6".

### **Outdoor Competition Sleeve and Cover Combo**

#### **MODEL NO. PK235**

##### **Floor Sleeve**

Aluminum sleeve shall be 9" long. Inside diameter of the sleeve shall be 3".

##### **Brass Cover Plate (VB235)**

Cover plate and outer ring shall be gold-plated machined aluminum with an outside diameter of 7.25" and a thickness of 5/8". Removable lid shall have a diameter of 5", and the opening shall be 4". Cover plate shall remain permanently attached to the floor sleeve by means of machine screws.